



# Stiesdal Mooring

Industrialized station keeping system for floating wind.

## Industrialized Mooring and Anchoring

Designed for scalable, repeatable, and low-cost offshore deployment.

## Gravity Anchor

Modular, seabed-agnostic, and designed for serial production and local fabrication using existing infrastructure.

## Efficient and Unmanned Installation

Hook-up and tensioning are fully ROV executed, with no personnel transfer or deck handling.

## Full Campaign in One Installation Season

Complete array installation within one campaign using shared-anchor setup.

## Cost Insight\*

~30 % lower mooring system cost

~5 % total project CAPEX saving

*Benefits increase with array scale*

\* Cost insight based on 500MW APAC project



Gravity anchor, design visualization

## Shared Anchoring

Deliver true farmscale efficiency, reducing anchor count by more than 80% at GW-projects while maintaining full redundancy

Based on a 6-3 configuration: six mooring lines per floater arranged in three shared pairs that converge at three anchors.



## The Anchor

- Modular gravity anchor enabling decoupled installation and ballasting.
- Multiple line connections from one or more floaters.
- Industrialized fabrication using regional yards and suppliers.
- Capable of full structural removal or re-purposing as an artificial reef.

# Stiesdal<sup>®</sup> Offshore

Stiesdal Offshore A/S / Hedeager 1, 8200 Aarhus N, Denmark

[www.stiesdal.com/offshore](http://www.stiesdal.com/offshore)  
[info@stiesdal.com](mailto:info@stiesdal.com)

©2025 Stiesdal A/S. All rights reserved.

All specifications in this document are for information only and are subject to change without notice. No expressed or implied representations or warranties regarding the adequacy or accuracy of the information are given. Certain options may not be available in all locations or countries.

